

## Dixon Keychain

**Feature:**

- halves separate like a coupler and plug

Plated Steel Part #	Price/E
<b>DKC1</b>	<b>\$20.50</b>



## Breather Vents

**Applications:**

- commonly used on single acting cylinders or valves to prevent dirt and foreign particles from entering ports open to the atmosphere additionally
- provide vacuum relief or pressure equalization on gear boxes, oil tanks or reservoirs

**Features:**

- standard pipe thread connections for quick assembly and removal for cleaning
- nickel plated steel insert with a bronze filter
- 40 micron filter element
- maximum operating pressure: **150 PSI**
- temperature range: **35°F to 300°F**

NPT Thread	Overall Length	Nickel Plated Steel Part #	Price/E
1/8"	7/16"	<b>ASP-1BV</b>	<b>\$2.50</b>
1/4"	5/8"	<b>ASP-2BV</b>	<b>2.60</b>
3/8"	3/4"	<b>ASP-3BV</b>	<b>3.75</b>
1/2"	7/8"	<b>ASP-4BV</b>	<b>5.50</b>
3/4"	1"	<b>ASP-6BV</b>	<b>8.90</b>
1"	1-5/16"	<b>ASP-8BV</b>	<b>17.20</b>



F

## Conical Mufflers

**Application:**

- threads into the exhaust ports of air tool, valves, cylinders and other pneumatic equipment

**Features:**

- an economical way to reduce noise levels below 90 dBA to conform with OSHA standards
- 40 micron bronze filter element
- element is bonded directly to the fitting and *is not replaceable*
- maximum operating pressure: **300 PSI**
- temperature range: **35°F to 300°F**

NPT Thread	Overall Length	Nickel Plated Steel Part #	Price/E
1/8"	1-1/8"	<b>CMF18</b>	<b>\$3.60</b>
1/4"	1-3/8"	<b>CMF28</b>	<b>4.30</b>
3/8"	1-1/2"	<b>CMF38</b>	<b>5.60</b>
1/2"	1-7/8"	<b>CMF48</b>	<b>8.65</b>
3/4"	2-1/8"	<b>CMF68</b>	<b>14.30</b>
1"	2-7/8"	<b>CMF88</b>	<b>20.50</b>



## Speed Control Mufflers

**Features:**

- maximum operating pressure: **300 PSI**
- temperature range: **35°F to 300°F**
- safe and infinite variations of metering air flow at acceptable sound levels on exhaust ports of air valves.
- speed of operating cylinder or air tool may be increased or decreased with adjusting screw, the final position is locked in place by the lock nut.
- exhaust air noise is eliminated by a surrounding sleeve of sintered bronze

NPT Thread	Approximate Full Operating Height	Maximum Adjusted SCFM	2011T3 Aluminum <sup>1</sup>		Brass	
			Part #	Price/E	Part #	Price/E
1/8"	1-5/16"	20	<b>ASCM18</b>	<b>\$8.00</b>	<b>SCM18</b>	<b>\$6.55</b>
1/4"	1-9/16"	30	---	---	<b>SCM28</b>	<b>7.55</b>
3/8"	1-5/8"	40	<b>ASCM38</b>	<b>12.10</b>	<b>SCM38</b>	<b>10.90</b>
1/2"	2"	60	<b>ASCM48</b>	<b>16.50</b>	<b>SCM48</b>	<b>16.90</b>
3/4"	2-3/8"	70	<b>ASCM68</b>	<b>28.95</b>	<b>SCM68</b>	<b>22.50</b>
1"	2-1/2"	100	---	---	<b>SCM88</b>	<b>41.00</b>

<sup>1</sup> stock quantity only


aluminum



brass